


**Panel mounted receptacle - Part no. 1468**


- screw terminals
- suitable for through wiring
- 20° inclination

**Technical information**

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 16 A            |
| Poles                 | 4 p             |
| Voltage               | 500V            |
| Earth position        | 7 h             |
| Hertz                 | 50-60 Hz        |
| Connection technology | Screw terminals |
| Contact               | standard        |
| Protection type       | IP 44           |



| Drawing<br>1 MB 260 | Amp.<br>Poles   | 16   |     |     | 32  |     |     |
|---------------------|---|------|-----|-----|-----|-----|-----|
|                     |   | 3    | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm          | a   | 73.5 | 100 | 100 | 100 | 100 | 100 |
|                     | b   | 64   | 92  | 92  | 92  | 92  | 92  |
|                     | c   | 50   | 59  | 58  | 62  | 62  | 61  |
|                     | d   | 60   | 85  | 85  | 85  | 85  | 85  |
|                     | e   | 52   | 77  | 77  | 77  | 77  | 77  |
|                     | f   | 5.5  | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 |
|                     | g   | 7    | 8   | 8   | 8   | 8   | 8   |
|                     | g-1   | 2    | 2   | 2   | 2   | 2   | 2   |
|                     | h   | 79   | 100 | 100 | 103 | 103 | 106 |
|                     | k   | 44   | 34  | 34  | 54  | 54  | 49  |
|                     | l   | 52   | 55  | 65  | 67  | 67  | 72  |
|                     | ll  | 60   | 63  | 72  | 82  | 82  | 85  |
|                     | o   | 20°  | 20° | 20° | 20° | 20° | 20° |
|                     | Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. | 1.5  | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
|                     |   | -4   | -4  | -4  | -10 | -10 | -10 |